

Prediction of broadband noise in internal flows

C. Schram *

13 March 2009

Contents

1	Introduction	3
2	Aeroacoustical analogy	5
2.1	Lighthill's analogy	5
2.2	Curle's analogy	10
2.3	Ffowcs Williams & Hawkings analogy	12
3	Numerical acoustics in a nutshell	15
3.1	Finite Element Method vs. Boundary Element Method	15
3.2	Finite Element Method	16
3.3	Boundary Element Method	17
4	BEM / Curle formulation	21
4.1	Reminder	21
4.2	Boundary integral form	22
5	Numerical aspects	27
5.1	Conservative mesh mapping	27
5.1.1	Conservative mapping techniques	27
5.1.2	Mapping on a flat surface	29
5.1.3	Influence of the surface orientation	31
5.2	Truncation of the quadrupolar field	32
5.2.1	Correction of the truncation error	32
5.2.2	Windowing techniques	34
6	Examples	37
6.1	Free cylinder in crossflow	37
6.1.1	Flow computation	37
6.1.2	Acoustic computation	39
6.2	Ducted spinning vortex pair	41
6.2.1	Flow model	42

*Aeroacoustics Project Leader, LMS International

6.2.2	Two-dimensional tailored Green's function	45
6.2.3	Application of the BEM/Curle formulation	46
6.2.4	Sampling and integration of the dipoles and quadrupoles	46
6.2.5	Non-reflecting boundary conditions	46
6.2.6	Sound emitted by the ducted spinning vortex pair	48

Acknowledgements

I gratefully acknowledge the contributions of Mrs Paula Martinez and Prof Wim Desmet to the present lecture notes material.